

View Online at <https://aerobasegroup.com/nsn/5962-01-262-2721>

Body Length:

0.350 inches

Body Width:

0.350 inches

Maximum Power Dissipation Rating:

0.6 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and bipolar and programmable

Inclosure Material:

Metal or plastic or ceramic

Inclosure Configuration:

Leaded chip carrier

Output Logic Form:

Bipolar metal-oxide semiconductor

Input Circuit Pattern:

16 input

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

12.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Memory Device Type:

Pal

Precious Material And Location:

Terminal surface option gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0