## NSN 5962-01-262-2722

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-262-2722 **Body Length:** 1.060 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 0.6 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and bipolar and programmable **Inclosure Material:** Metal or plastic or ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Bipolar metal-oxide semiconductor **Input Circuit Pattern:** 16 input **Case Outline Source And Designator:** D-8 mil-m-38510 **Current Rating Per Characteristic:** 12.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Memory Device Type:** Pal **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5962-01-262-2722

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0