

View Online at <https://aerobasegroup.com/nsn/5962-01-262-7992>

**Body Length:**

1.480 inches

**Body Width:**

0.610 inches

**Body Height:**

0.180 inches

**Maximum Power Dissipation Rating:**

400.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and monolithic and w/enable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

5 input and 16 channel

**Design Function And Quantity:**

1 multiplexer/demultiplexer, analog

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

32.0 volts power source

**Time Rating Per Characteristic:**

1500.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

28 printed circuit

**Specification Data:**

81349-mil-m-38510/190 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0