NSN 5962-01-263-0966

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-263-0966

view Orinite at https://derobasegroup.com/hsr//0902-01-200-0900
Body Length:
0.540 inches
Body Width:
Between 0.245 inches and 0.300 inches
Body Height:
Between 0.045 inches and 0.092 inches
Maximum Power Dissipation Rating:
220.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and schottky and w/clear and w/clock and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
8 input
Design Function And Quantity:
1 shift register, universal, shift storage
Case Outline Source And Designator:
F-9 mil-m-38510
Terminal Surface Treatment:
Gold or solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Special Features:
Nuclear hardness critical items
Nuclear Hardness Critical Feature:
Hardened
Precious Material And Location:
Terminal surfaces option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

20 flat leads

NSN 5962-01-263-0966

Digital Microcircuit - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0