NSN 5962-01-263-0982



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-263-0982 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 187.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 adder, full, binary **Case Outline Source And Designator:** F-5 mil-m-38510 **Current Rating Per Characteristic:** 18.00 milliamperes supply **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts input **Time Rating Per Chacteristic:** 41.00 nanoseconds propagation delay time, low to high level output and 41.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-263-0982

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0