NSN 5962-01-263-2881

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-263-2881

| view Online at https://aerobasegroup.com/hsn/5962-01-265-2661 |
|--|
| Body Length: |
| 0.785 inches |
| Body Width: |
| 0.310 inches |
| Body Height: |
| 0.185 inches |
| Maximum Power Dissipation Rating: |
| 200.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| Triple 3 input |
| Design Function And Quantity: |
| 3 gate, nor |
| Case Outline Source And Designator: |
| D-1 mil-m-38510 |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 15.5 volts power source |
| Precious Material And Location: |
| Terminal surfaces gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Specification Data: |
| 81349-mil-m-38510/52 government specification |

N/a

Shelf Life:

NSN 5962-01-263-2881

Digital Microcircuit - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0