NSN 5962-01-263-2888

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-263-2888 **Body Length:** 0.350 inches **Body Width:** 0.350 inches **Body Height:** 0.100 inches **Maximum Power Dissipation Rating:** 12.3 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and low power and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Triple 3 input **Design Function And Quantity:** 3 gate, and **Case Outline Source And Designator:** C-2 mil-m-38510 **Current Rating Per Characteristic:**

1.80 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts low level output and 7.0 volts power source

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

81349-mil-m-38510/374 government specification

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-263-2888

Digital Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0