NSN 5962-01-263-6059

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-263-6059

view Online at https://aerobasegroup.com/nsn/5962-01-265-6059
Body Length:
2.020 inches
Body Width:
0.620 inches
Body Height:
0.155 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and programmable and w/clock and w/clear
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
21 input
Criticality Code Justification:
Zzzy
Design Function And Quantity:
1 receiver, asynchronous and 1 transmitter
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
450.00 nanoseconds propagation delay time, low to high level output and 450.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3802.
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
40 printed circuit

Reference number differentiatingmaterial will be in accordance with naval inventory control point hx quality control. Manufacturing and testing

Shelf Life:

Reference Number Differentiating Characteristics:

specifications available at the dla icp.

N/a

NSN 5962-01-263-6059

Digital Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0