NSN 5962-01-263-9182

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-263-9182

Overall Length: 0.840 inches **Overall Height:** Between 0.325 inches and 0.400 inches **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Programmable and w/clock and w/enable and w/reset **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 8 input **Design Function And Quantity:** 1 generator **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 1500.00 microamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Bit rate generator Voltage Rating And Type Per Characteristic: 8.0 volts power source **Time Rating Per Chacteristic:**

300.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

NSN 5962-01-263-9182

Digital Microcircuit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0