

View Online at <https://aerobasegroup.com/nsn/5962-01-263-9387>

Body Length:

0.840 inches

Body Width:

0.260 inches

Body Height:

0.085 inches

Maximum Power Dissipation Rating:

400.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

1 channel and 1 input

Design Function And Quantity:

1 switch, driver

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Gold or solder or tin

Voltage Rating And Type Per Characteristic:

33.0 volts power source

Time Rating Per Characteristic:

600.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface option gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0