

View Online at <https://aerobasegroup.com/nsn/5962-01-263-9894>

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.100 inches

Maximum Power Dissipation Rating:

468.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and schottky and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

12 input

Design Function And Quantity:

1 selector, data, multiplexer

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

85.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

26.00 nanoseconds propagation delay time, low to high level output and 28.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A458a0