Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-264-0723

Body	Length:
0.280	inches
Body	Width:
	inches
Body	Height:
0.085	inches
Maxir	num Power Dissipation Rating:
350.0	milliwatts
Opera	ating Tempurature Range:
-55.0/	+125.0 degrees celsius
Stora	ge Tempurature Range:
-65.0/	+150.0 degrees celsius
Featu	res Provided:
Herm	etically sealed and burn in and monolithic and positive outputs
Inclos	sure Material:
Cerar	nic and glass
Inclos	sure Configuration:
Flat p	ack
Input	Circuit Pattern:
1 cha	nnel and 1 input
Desig	n Function And Quantity:
1 swit	ch, driver
Case	Outline Source And Designator:
F-1 m	il-m-38510
Term	inal Surface Treatment:
Solde	r
Volta	ge Rating And Type Per Characteristic:
33.0 \	volts power source
Time	Rating Per Chacteristic:
400.0	0 nanoseconds propagation delay time, low to high level output and 550.00 nanoseconds propagation delay time, high to low level
outpu	t
Test I	Data Document:
96906	o-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Term	inal Type And Quantity:
14 fla	t leads
Shelf	Life:
N/a	
Unit C	Of Measure:
Demi	litarization:
Yes -	demil/mli
Fiig:	
A458a	aO