

View Online at <https://aerobasegroup.com/nsn/5962-01-264-1997>

Body Length:

1.060 inches

Body Width:

0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and w/enable and w/strobe and electrostatic sensitive

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 driver, bus

Case Outline Source And Designator:

D-8 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

8.0 volts total supply

Time Rating Per Characteristic:

55.00 nanoseconds propagation delay time, low to high level output and 55.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0