NSN 5962-01-264-1999

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-264-1999 **Body Length:** 0.785 inches **Body Width:** 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/strobe and w/inhibit **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 6 input **Criticality Code Justification:** Zzzy **Design Function And Quantity:** 1 decoder, four to sixteen line and 1 latch **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 20.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit **Reference Number Differentiating Characteristics:** Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control, manufacturing and testing specifications available at the dla icp Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-264-1999

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0