

View Online at <https://aerobasegroup.com/nsn/5962-01-264-2000>

**Body Length:**

2.020 inches

**Body Width:**

0.620 inches

**Body Height:**

0.135 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and w/clock and bidirectional

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

18 input

**Criticality Code Justification:**

Zzzy

**Design Function And Quantity:**

1 microprocessor

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

850.00 nanoseconds propagation delay time, low to high level output and 850.00 nanoseconds propagation delay time, high to low level output

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3817

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

40 printed circuit

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0