Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-264-2712

Body Length:	
0.985 inches	
Body Width:	
0.280 inches	
Body Height:	
0.160 inches	
	Dissipation Rating:
1667.0 milliwatts	Diosipation Rating.
Operating Tempu	Irature Range:
-0.0/+70.0 degrees	
Storage Tempura	
-65.0/+150.0 degre	
Features Provide	
	schottky and high speed and 3-state output
Inclosure Materia	
Ceramic and glass	
Inclosure Config	
Dual-in-line	
Output Logic For	m:
Transistor-transist	
Input Circuit Patt	
10 input	
Design Function	And Quantity:
8 transceiver	
Terminal Surface	Treatment:
Solder	
Voltage Rating A	nd Type Per Characteristic:
7.0 volts power so	Durce
Time Rating Per	Chacteristic:
23.00 nanosecond	Is propagation delay time, low to high level output and 23.00 nanoseconds propagation delay time, high to low level
output	
Test Data Docum	ient:
96906-mil-std-883	standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type Ar	nd Quantity:
20 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	