

View Online at <https://aerobasegroup.com/nsn/5962-01-264-2980>

**Body Length:**

Between 0.342 inches and 0.358 inches

**Body Width:**

Between 0.342 inches and 0.358 inches

**Body Height:**

Between 0.064 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

88.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Low power and schottky and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Hex 2 input

**Design Function And Quantity:**

6 driver, or

**Case Outline Source And Designator:**

C-2 mil-m-38510

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Special Features:**

Nuclear hardness critical items

**Nuclear Hardness Critical Feature:**

Hardened

**Precious Material And Location:**

Terminal surfaces option gold

**Precious Material:**

Gold

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0