

View Online at <https://aerobasegroup.com/nsn/5962-01-264-2987>

**Body Length:**

0.440 inches

**Body Width:**

Between 0.245 inches and 0.285 inches

**Body Height:**

Between 0.045 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

77.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Low power and schottky and monolithic and 3-state output

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

12 input

**Design Function And Quantity:**

2 selector, data, multiplexer, four to one line

**Case Outline Source And Designator:**

F-5 mil-m-38510

**Current Rating Per Characteristic:**

4.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 flat leads

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0