NSN 5962-01-264-3020

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-264-3020

Body Length:	
1.060 inches	
Body Width:	
0.310 inches	
Body Height:	
0.185 inches	
Maximum Power Dissipation Rating:	
1.1 watts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and programmable and positive outputs	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
14 input	
Design Function And Quantity:	
1 gate, array	
Case Outline Source And Designator:	
D-8 mil-m-38510	
Current Rating Per Characteristic:	
90.00 milliamperes supply	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
12.0 volts total supply	
Time Rating Per Chacteristic:	
50.00 nanoseconds propagation delay time, low to high level output an	d 50.00 nanoseconds propagation delay time, high to low level
output	
Test Data Document:	
81349-mil-m-38510 specification (includes engineering type bulletins, b	rochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar	trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that a	re shown as "tynical" "average" "" etc)

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 pin

Specification Data:

81349-mil-m-38510/504 government specification

Shelf Life:

NI/o

NSN 5962-01-264-3020

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A458a0

