

View Online at <https://aerobasegroup.com/nsn/5962-01-264-3025>

**Body Length:**

Between 1.980 inches and 2.020 inches

**Body Width:**

Between 0.582 inches and 0.610 inches

**Body Height:**

Between 0.072 inches and 0.090 inches

**Maximum Power Dissipation Rating:**

1000.0 milliwatts

**Operating Temperature Range:**

-55.0 to 125.0 degrees celsius

**Storage Temperature Range:**

-65.0 to 150.0 degrees celsius

**Features Provided:**

Monolithic and w/clock and hermetically sealed and electrostatic sensitive

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

12 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

1 converter, analog to digital

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

14.0 volts power source

**Time Rating Per Characteristic:**

500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output

**Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L03842; for nuclear propulsion plant products only

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

40 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0