NSN 5962-01-264-4465

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-264-4465

| Dedu Lengt | b . |
|---------------|--|
| Body Lengtl | |
| 0.560 inches | |
| Body Width: | |
| 0.450 inches | |
| Body Height | |
| 0.085 inches | |
| | ower Dissipation Rating: |
| 750.0 milliwa | |
| | empurature Range: |
| | degrees celsius |
| | npurature Range: |
| | degrees celsius |
| Features Pro | |
| Hermetically | sealed and burn in and programmable and erasable and w/buffered output and bidirectional |
| Inclosure Ma | aterial: |
| Ceramic | |
| Inclosure Co | onfiguration: |
| Leadless flat | pack |
| Output Logi | c Form: |
| N-type metal | oxide-semiconductor logic |
| Input Circuit | t Pattern: |
| 24 input | |
| Terminal Su | rface Treatment: |
| Solder | |
| Voltage Rati | ing And Type Per Characteristic: |
| -0.3 volts po | wer source and 6.0 volts power source |
| Memory Dev | vice Type: |
| Rom | |
| Memory Cap | pacity: |
| Unknown | |
| Test Data Do | ocument: |
| 96906-mil-sto | d-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Ty | pe And Quantity: |
| 32 leadless | |
| Shelf Life: | |
| N/a | |
| Unit Of Mea | sure: |
| | |
| Demilitariza | tion: |
| Yes - demil/n | |
| Fiig: | |
| A458a0 | |