NSN 5962-01-264-5230

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-264-5230 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.140 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** 3-state output and high speed and low power and schottky **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 8 flip-flop, d-type **Case Outline Source And Designator:** D-8 mil-m-38510 **Current Rating Per Characteristic:** 160.00 microamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts total supply **Time Rating Per Chacteristic:** 54.00 nanoseconds propagation delay time, low to high level output and 54.00 nanoseconds propagation delay time, high to low level output **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 pin

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-264-5230

Digital Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0