NSN 5962-01-264-5248

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-264-5248

view Offilite at https://aerobasegroup.com/nsn/3302-01-204-3240
Body Length:
Between 0.745 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.055 inches and 0.140 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and low current
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Hex 1 input
Criticality Code Justification:
Feat
Design Function And Quantity:
6 buffer
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 20.0 volts power source
Special Features:
Item must comply with requirements of defense electronics supply center production standard no. L03827; for nuclear propulsion plant
products only
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-264-5248

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0