

View Online at <https://aerobasegroup.com/nsn/5962-01-264-5447>

Overall Height:

Between 0.357 inches and 0.432 inches

Body Length:

1.490 inches

Body Width:

Between 0.500 inches and 0.610 inches

Body Height:

Between 0.172 inches and 0.217 inches

Maximum Power Dissipation Rating:

1.0 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and programmable and ultraviolet erasable and w/enable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

17 input

Case Outline Source And Designator:

D-10 mil-m-38510

Current Rating Per Characteristic:

50.00 milliamperes supply

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

0.6 volts total supply and 6.3 volts total supply

Time Rating Per Characteristic:

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Prom

Memory Capacity:

Unknown

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0