

View Online at <https://aerobasegroup.com/nsn/5962-01-264-9830>

**Body Length:**

0.770 inches

**Body Width:**

0.260 inches

**Body Height:**

0.180 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Aircraft, viking s-3b; aircraft, hawkeye e-2c; ta-4j aircraft; aircraft, harrier av-8b; aircraft, b-2 bomber (atb); aircraft, hercules c-130; aircraft, hornet f/a-18; aircraft, galaxy c-5; nuclear power plants

**Features Provided:**

Hermetically sealed and burn in and high voltage and electrostatic sensitive

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Quad 2 input

**Criticality Code Justification:**

Zzzy

**Design Function And Quantity:**

4 schmitt trigger

**Case Outline Source And Designator:**

Mo-001ab joint electron device engineering council

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

20.0 volts power source

**Time Rating Per Characteristic:**

600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level output

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard lo3851

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0