NSN 5962-01-264-9836



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-264-9836 **Body Length:** 0.785 inches **Body Width:** 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and positive outputs and dynamic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 8 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 6 buffer **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 20.0 volts power source **Special Features:** Item must comply with requirements of defense electronics supply center production standard no. L03854; for navy nuclear propulsion plant products only **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-264-9836

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0