## NSN 5962-01-264-9837

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-264-9837

| Body Length:  |
|---|
| 0.785 inches  |
| Body Width:   |
| 0.260 inches  |
| Body Height:  |
| 0.180 inches  |
| Maximum Power Dissipation Rating:   |
| 500.0 milliwatts  |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and burn in and w/clock and w/enable and w/reset  |
| Inclosure Material:   |
| Ceramic   |
| Inclosure Configuration:  |
| Dual-in-line Dual-in-line   |
| Output Logic Form:  |
| Complementary-metal oxide-semiconductor logic   |
| Input Circuit Pattern:  |
| Dual 3 input  |
| Criticality Code Justification:   |
| Zzzy  |
| Design Function And Quantity:   |
| 2 counter   |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| -0.5 volts power source and 20.0 volts power source   |
| Time Rating Per Chacteristic:   |
| 550.00 nanoseconds propagation delay time, low to high level output and 550.00 nanoseconds propagation delay time, high to low level          |
| output  |
| Test Data Document:   |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).                            |
| Terminal Type And Quantity:   |
| 16 printed circuit  |
| Reference Number Differentiating Characteristics:   |
| Reference number differentiating material will be accordance with naval inventory control point activity hx quality control manufacturing and |
| testing specifications available at the dla icp   |

--

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5962-01-264-9837

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0