NSN 5962-01-265-0351

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-265-0351 **Body Length:** Between 0.753 inches and 0.785 inches **Body Width:** Between 0.265 inches and 0.285 inches **Body Height:** Between 0.140 inches and 0.170 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and low power and high frequency **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Criticality Code Justification:** Zzzy **Design Function And Quantity:** 2 switch, analog, single pole single throw normally open **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 44.0 volts power source **Special Features:** Item must comply with requirements of defense supply center columbus production standard lo3853 **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-265-0351

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0