

View Online at <https://aerobasegroup.com/nsn/5962-01-265-2209>

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.140 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

3-state output and high speed and monolithic and w/enable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Design Function And Quantity:

8 latch

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

160.00 microamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

53.00 nanoseconds propagation delay time, low to high level output and 53.00 nanoseconds propagation delay time, high to low level output

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufacturer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0