## NSN 5962-01-265-4709

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-265-4709

Body	Length:

- 0.785 inches
- **Body Width:**
- 0.310 inches

### Body Height:

0.185 inches

#### **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Monolithic

#### **Inclosure Material:**

inclosule

### Ceramic

Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

Hex 1 input

#### **Design Function And Quantity:**

6 inverter

#### **Case Outline Source And Designator:**

D-1 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

6.0 volts power source

#### **Time Rating Per Chacteristic:**

11.00 nanoseconds propagation delay time, low to high level output and 10.00 nanoseconds propagation delay time, high to low level

output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

14 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# NSN 5962-01-265-4709

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

