## NSN 5962-01-265-5966

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-265-5966 **Body Length:** 0.810 inches **Body Width:** 0.510 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and hybrid and thin film and precision **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 1 reference, voltage, analog **Current Rating Per Characteristic:** 17.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 20.0 volts power source **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-265-5966

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0