NSN 5962-01-266-1443

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-266-1443

Body Length:
Between 0.540 inches and 0.560 inches
Body Width:
Between 0.442 inches and 0.458 inches
Body Height:
Between 0.060 inches and 0.120 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and erasable and w/enable and programmable
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
C-12 mil-m-38510
Current Rating Per Characteristic:
140.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 6.5 volts power source
Capitance Rating Per Characteristic:
10.00 input picofarads and 12.00 output picofarads
Memory Device Type:
Eeprom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
32 leadless
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-266-1443

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0