## NSN 5962-01-266-1906

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-266-1906 **Body Length:** 0.350 inches **Body Width:** 0.350 inches **Body Height:** 0.100 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and high speed **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 shift register **Case Outline Source And Designator:** C-2 mil-m-38510 **Current Rating Per Characteristic:** 35.00 milliamperes forward current, peak total value not applicable **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts total supply **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5962-01-266-1906

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0