NSN 5962-01-266-3209

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-266-3209

| Body Length: |
|--|
| Between 0.540 inches and 0.560 inches |
| Body Width: |
| Between 0.442 inches and 0.458 inches |
| Body Height: |
| Between 0.060 inches and 0.120 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and erasable and w/enable and programmable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leadless flat pack |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 16 input |
| Case Outline Source And Designator: |
| C-12 mil-m-38510 |
| Precious Material And Location: |
| Terminal surfaces option gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |