NSN 5962-01-266-8049

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-266-8049

Body Length:
0.185 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.140 inches
Maximum Power Dissipation Rating:
24.6 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low power and schottky and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 gate, inverting
Case Outline Source And Designator:
D-1 mil-m-38510
Current Rating Per Characteristic:
-110.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Special Features:
Nuclear hardness critical items
Nuclear Hardness Critical Feature:
Hardened
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 printed circuit

81349-mil-m-38510/370 government specification

Specification Data:

NSN 5962-01-266-8049

Digital Microcircuit - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0