## NSN 5962-01-266-8062

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-266-8062

Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
0.150 inches
Maximum Power Dissipation Rating:
1.88 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Features Provided:
Hermetically sealed and programmable and ultraviolet erasable and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Metal oxide-semiconductor logic
Input Circuit Pattern:
14 input
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
450.00 nanoseconds propagation delay time, low to high level output and 450.00 nanoseconds propagation delay time, high to low leve
output
Memory Device Type:
Rom
Precious Material And Location:
Terminal surfaces option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit

N/a

Shelf Life:

## NSN 5962-01-266-8062

Memory Microcircuit - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0