NSN 5962-01-266-9029

Linear Microcircuit - Page 1 of 2



plant

View Online at https://aerobasegroup.com/nsn/5962-01-266-9029

Body Length:	
0.785 inches	
Body Width:	
0.310 inches	
Body Height:	
0.185 inches	
Maximum Power Dissipation Rating:	
500.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and low voltage and low noise and internally compensated	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Input Circuit Pattern:	
Dual 2 input	
Criticality Code Justification:	
Feat	
Design Function And Quantity:	
2 amplifier, operational, instrumentation	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
22.0 volts power source	
Special Features:	
Item must comply with requirements of defense electronics supply center production standard no. Lo3895; for navy nuclear production sta	oropulsion (
products only	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	
Terminal Type And Quantity:	
14 printed circuit	
Reference Number Differentiating Characteristics:	
Reference number differentiating materil will be iaw navicp, hx quality control, mfg and testing specs available the the dla icp	р
Shelf Life:	
N/a	
Unit Of Measure:	

Demilitarization:

Yes - demil/mli

NSN 5962-01-266-9029

Linear Microcircuit - Page 2 of 2

Fiig: A458a0

