

View Online at <https://aerobasegroup.com/nsn/5962-01-266-9981>

Body Length:

1.290 inches

Body Width:

0.295 inches

Body Height:

0.205 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and electrostatic sensitive and w/strobe and w/inhibit

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

6 input

Criticality Code Justification:

Zzzy

Design Function And Quantity:

1 decoder, four to sixteen line and 1 latch

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 18.0 volts power source

Time Rating Per Characteristic:

1100.00 nanoseconds propagation delay time, low to high level output and 1100.00 nanoseconds propagation delay time, high to low level output

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3888

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0