NSN 5962-01-267-0885

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-267-0885

Body Length:
0.785 inches
Body Width:
0.291 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and resettable and retriggerable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Dual 3 input
Criticality Code Justification:
Zzzy
Design Function And Quantity:
2 multivibrator, monostable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 15.0 volts power source
Time Rating Per Chacteristic:
600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Item must comply with requirements of defense supply center (columbus) production standard no. (I03883)

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control, manufacturing and testing specifications available at the dla icp.

Shelf Life:

NSN 5962-01-267-0885

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

