NSN 5962-01-267-0962

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-267-0962 **Body Length:** 0.840 inches **Body Width:** 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 4 flip-flop, d-type **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 35.00 milliamperes forward current, peak total value not applicable **Terminal Surface Treatment:** Tin **Voltage Rating And Type Per Characteristic:** 7.0 volts input **Time Rating Per Chacteristic:** 265.00 nanoseconds propagation delay time, low to high level output and 265.00 nanoseconds propagation delay time, high to low level

output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-267-0962

Digital Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0