NSN 5962-01-267-3833

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-267-3833

Body Length:
Between 0.342 inches and 0.358 inches
Body Width:
Between 0.342 inches and 0.358 inches
Body Height:
Between 0.064 inches and 0.100 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and burn in
Inclosure Material:
Metal
Inclosure Configuration:
Leadless flat pack
Input Circuit Pattern:
Quad 1 input
Design Function And Quantity:
4 receiver, line
Case Outline Source And Designator:
C-2 mil-m-38510
Terminal Surface Treatment:
Gold
Voltage Rating And Type Per Characteristic:
10.0 volts power source
Time Rating Per Chacteristic:
85.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level
output
Precious Material And Location:
Terminal surfaces option gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 leadless

__

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-267-3833

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0