## NSN 5962-01-267-8167

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-267-8167

## **Body Length:** 1.490 inches **Body Width:** 0.610 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4920-01-148-5597 test station, av **Features Provided:** Hermetically sealed and burn in and ultraviolet erasable and programmable and w/enable **Inclosure Material:** Ceramic and glass Inclosure Configuration: Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 17 input **Case Outline Source And Designator:** D-10 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 6.0 volts power source **Time Rating Per Chacteristic:** 450.00 nanoseconds propagation delay time, low to high level output and 450.00 nanoseconds propagation delay time, high to low level output Memory Device Type: Rom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a Unit Of Measure:

## NSN 5962-01-267-8167

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

