NSN 5962-01-268-7770

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-268-7770

| view Offilite at https://defobasegroup.com/his//0302-01-200-7770 |
|--|
| Body Length: |
| 0.840 inches |
| Body Width: |
| 0.310 inches |
| Body Height: |
| 0.185 inches |
| Maximum Power Dissipation Rating: |
| 300.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 5805-01-216-0887 switchboard tel |
| Features Provided: |
| Hermetically sealed and burn in and w/clock and w/clear and w/preset and high speed |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| Dual 5 input |
| Design Function And Quantity: |
| 2 flip-flop, j-k |
| Case Outline Source And Designator: |
| D-2 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Specification Data: |
| 81349-mil-m-38510/653 government specification |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5962-01-268-7770

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0