## NSN 5962-01-271-6078

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-271-6078 **Body Length:** 0.980 inches **Body Width:** 0.805 inches **Body Height:** 0.190 inches **Maximum Power Dissipation Rating:** 2.6 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **End Application:** 6675-01-179-2982 module, north fi **Features Provided:** Hermetically sealed and burn in and hybrid and frequency compensated **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 17.0 volts power source **Time Rating Per Chacteristic:** 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

## **Demilitarization:**

Yes - demil/mli

Fiig:

A458a0