Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-272-0122

# Body Length:

2.000 inches

### **Body Width:**

0.600 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

### **End Application:**

5805-01-216-0887 switchboard tel

### **Features Provided:**

Hermetically sealed and burn in and bidirectional and positive outputs

### Inclosure Material:

Ceramic

### Inclosure Configuration:

Dual-in-line

### Output Logic Form:

Complementary-metal oxide-semiconductor logic

### Input Circuit Pattern:

22 input

## **Design Function And Quantity:**

1 buffer

## **Terminal Surface Treatment:**

Gold

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

# Precious Material And Location:

Terminal surfaces gold

# Precious Material:

Gold

# Test Data Document:

80372-755090a0222 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

40 printed circuit

# Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

### Fiig:

A458a0