NSN 5962-01-274-4200

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-274-4200

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.100 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and electrostatic sensitive and w/enable

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Input Circuit Pattern:

3 input and 8 channel

Design Function And Quantity:

2 multiplexer/demultiplexer, analog

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

44.0 volts power source

Time Rating Per Chacteristic:

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0