# NSN 5962-01-274-4209

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-274-4209

# **Body Length:**

Between 0.342 inches and 0.358 inches

## Body Width:

Between 0.342 inches and 0.358 inches

## **Body Height:**

Between 0.064 inches and 0.080 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Electrostatic sensitive and monolithic and hermetically sealed and high speed

#### **Inclosure Material:**

Ceramic or metal

#### **Inclosure Configuration:**

Leadless flat pack

# Output Logic Form:

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

Dual 4 input

#### **Design Function And Quantity:**

2 gate, and

# **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

7.0 volts power source

#### **Time Rating Per Chacteristic:**

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

#### Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

20 leadless

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0