NSN 5962-01-274-6439

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-274-6439 **Body Length:** 0.390 inches **Body Width:** Between 0.235 inches and 0.260 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 82.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Cascadable and low power and schottky and presettable and monolithic **Inclosure Material:** Ceramic or glass or metal **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 8 input **Design Function And Quantity:** 1 counter, presettable **Case Outline Source And Designator:** F-2 mil-m-38510 **Current Rating Per Characteristic:** 27.00 milliamperes supply **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Special Features:** Cascadable **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:**

14 flat leads

Specification Data:

81349-mil-m-38510/320 government specification

Shelf Life:

N/a

NSN 5962-01-274-6439

Digital Microcircuit - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A458a0