## NSN 5962-01-274-7048

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-274-7048 **Body Length:** Between 0.342 inches and 0.358 inches **Body Width:** Between 0.342 inches and 0.358 inches **Body Height:** Between 0.064 inches and 0.100 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and monolithic and high performance and hermetically sealed **Inclosure Material:** Ceramic or metal **Inclosure Configuration:** Leadless flat pack **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 switch, single pole single throw normally open **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 36.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A458a0