

View Online at <https://aerobasegroup.com/nsn/5962-01-274-7051>

Body Length:

0.840 inches

Body Width:

0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and w/strobe and w/clock and w/clear

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

10 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 multiplier, binary

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

20.0 volts power source

Time Rating Per Characteristic:

220.00 nanoseconds propagation delay time, low to high level output and 220.00 nanoseconds propagation delay time, high to low level output

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L03950; for navy nuclear propulsion plant products only

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0